

## Ei146e

### Optical Smoke Alarm



- Optical sensor - quick response to slow smouldering fires
- Automatic dust compensation
- Mains powered with 9V Alkaline battery back-up
- Easi-fit base for quick and simple installation
- Kitemarked to BS EN14604:2005
- 5 year guarantee



### Description

The Ei146e Optical Smoke Alarm is a mains powered alarm with a 9V Alkaline battery back-up and contains a proven optical smoke chamber. The alarm features a new modern design and improved optical sensor with sealed insect mesh and automatic dust compensation for reduced false alarms. It is supplied with an easi-fit base to make it quick and simple to install. Compatible with the Ei168RC RadioLINK Base for wireless interconnection

### Technical

<b>Sensor Type</b>	Optical
<b>Supply Voltage (V)</b>	230
<b>Battery Type</b>	Alkaline PP3

<b>Indicators</b>	Green - Power / Red - Alarm or fault
<b>Voltage Type</b>	AC
<b>Power Consumption (W)</b>	0.75

### Dimensions & Weights

<b>Depth (mm)</b>	47
<b>Width (mm)</b>	148
<b>Packaged weight (kg)</b>	0.389

<b>Height (mm)</b>	148
<b>Product weight (kg)</b>	0.345

### Approvals & Warranty

<b>Certification/Approvals</b>	BS EN 14604:2005
<b>EAN Number</b>	5099383010206

<b>Warranty</b>	5 year warranty
-----------------	-----------------