

Datasheet					
Mod.	Dwg n.	Date	Check	Rev.	
P9GD	941306	19/10/2016	AC	0	

## FIRE EXTINGUISHER 9KG POWDER

# stored pressure type Certified PED 2014/68/EU and EN 3.7 Fire rating 55A – 233B – C




Organic solid materials wood, rubber, textiles, etc.



Flammable liquids, gasoline, oil, etc.



Flammable gases, methane, prophane.



### **Technical specification**

Cylinder diameter \_\_\_\_\_: 182 mm \_\_\_\_\_: Steel cylinder, brass valve Material\_ Operating pressure \_\_\_\_\_ : 15 bar at 20°C Test pressure \_\_\_ \_\_\_\_: 30 bar \_\_\_\_\_: > 55 bar Burst pressure \_\_\_ \_\_\_\_\_: -30°C + 60°C Temperature range\_ Extinguishing agent \_\_\_\_\_: ABC powder Propellent \_\_\_\_  $N_2 + He$ \_\_\_\_: 9 kg Nominal charge \_ Jet length

#### **Dimensions**

Height: 580 mm Diameter: 182 mm Weight: 14,5 kg


### **SPARE PARTS LIST**


Pos.	Description	Code
1	Complete valve	7203040
1A	Gauge	2120001
1B	Seal	2250008
1C	Fixed pin	2100010
1D	Safety pin	2100601
1E	Check valve	2170001
1F	Plug check valve	2220200
1 <b>G</b>	O-Ring Ø26x3	2090203
1H	Piston group	2380015
1I	Spring	2151200
1L	Tube holder	2160500
2	Dip tube	2230104
3	Cylinder	0010633
4	ABC powder	2020003
5	Complete hose	2330073
6	Label	-





The use of non original spare parts may cause malfunctions loss





#### **Maintenance and Guarantee**

Maintenance must be made periodically by, trained and certified staff, according to the local regulations of the country where it is located. The extinguisher is guaranteed for 24 months from the date of the supply. The guarantee includes, repairing or replacement for production defects, unit must be sent back to the factory free of charge, only when authorized written agreement with our sales office has been reached. The guarantee expires in case of tampering and bad maintenance made by not-authorized staff. It must be recharged only by staff authorized and certified by use only original extinguisher agent and spare parts.