

CODE: MBK13-020ABF-P1E

ERP: 0501079

Fire Extinguisher 2Lt ABF Portable

Fire Extinguisher 2Lt ABF - Wet Chemical with one seam vessel with INTERNAL PLASTIC LAYER and Pressure Gauge Safety Release Valve. METALLIC BRACKET INCLUDED



CHARACTERISTICS

Capacity	2Lt
Fire Ratings	5A 34B 40F
Extinguishing Agent	Eco Dare ABF -30°C/M
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	2,274 lt
Cylinder Height	310±5 mm
Cylinder Diameter	110±1 mm
Cylinder Neck Thread	M30x1,5
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	3,650 kg
Approx. Dimensions	400x140 mm
Paint Finish	RAL 3000
Packaging Details	6 pcs.



Issue Date: 13/12/2018

Information may change

FACTORY: AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

CENTRAL EXHIBITION: 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

ATHENS DISTRIBUTION CENTER: MAGOULA - ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

N.GREECE DISTRIB. CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

CENT. & EAST CRETE DISTRIB. CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

www.mobiak.gr