

# Reveal FirePRO X



The smallest, lightest, durable and affordable personal thermal imaging camera for firefighting. Easy to carry attached to the firefighter's uniform. Designed to be useful for every firefighter in every situation. Reveal FirePRO X is easy to use thanks to intuitive software to help you fight fires smarter, safer and quicker. The camera delivers 320 x 240 high-resolution and smooth thermal imaging. And, when you need it, a powerful 300-lumen LED light is available at the touch of a button. Reveal FirePRO X helps to find hot spots and heartbeats faster when every second counts. See through smoke, visualise your plan, and execute. Designed and Manufactured in Santa Barbara, California with Global Components.

## KEY FEATURES

### 320 x 240 Thermal Sensor

Excellent image clarity and sensitivity with 76,800 pixels

### Waterproof Design

Designed for the outdoors with IP67 rating

### Wide, 32-Degree Field of View

Easily scan a large area to identify hazards and heartbeats in seconds

### Long-Lasting Rechargeable Battery

Up to 3.5 hours of continuous thermal imaging

### 3 Modes. Purpose-Built for First Responders

Enhance your vision and situational awareness with a variety of colour modes

## BENEFITS

### Situational Awareness

Visualize hazards invisible to the human eye and navigate safely

### Affordable Personal TIC

Equip the entire department with the first affordable personal TIC

300 lumen LED flashlight available at the touch of a button

### Search and Rescue

Find victims and self-rescue faster with a reliable personal TIC

### Execute 360 Size-ups & Overhaul Faster

When seconds count, a Seek personal TIC saves time and lives

## TECHNICAL DATA

|                         |  |
|-------------------------|--|
| Thermal Sensor          | 320 x 240 (76,800 pixels)                      |
| Detection Distance      | 0.3 to 550 m                                   |
| Field of View           | Wide, 32 Degree FOV                            |
| Temperature Range       | -4 to 1,022F (-20 to 550C)                     |
| Operating Temp          | -4 to 140F (-20 to 60C) No time limit          |
| Operating Temp (10 min) | -4 to 185F (-20 to 85C) Up to 10 minutes       |
| Operating Temp (2 min)  | -4 to 225F (-20 to 107C) Up to 2 minutes       |
| Frame Rate              | >15 Hz FastFrame                               |
| IP Rating               | IP67 Waterproof                                |
| Flashlight              | 300 Lumen LED                                  |
| Display                 | 2.4" Colour with Corning® Gorilla® Glass       |
| Thermal Sensitivity     | < 70 mK  |
| User Interface          | Self-Contained Device with 3 Button Navigation |
| Temp. Display Scale     | Fahrenheit or Celsius                          |
| Color Filters           | 3 Options (FIRE, SURVEY, COLOR)                |
| Storage Media           | 4GB Internal Drive (>4,000 images)             |
| Battery                 | Up to 3.5 Hours Thermal Imaging                |
| Charging                | Magnetic charge port with sealed contacts      |

